

Ricoh D6520


Update your workstyle,
transform your teamwork

RICOH
imagine. change.

The Ricoh D6520 is the one-stop solution for collaboration your organisation needs. It enables better communication and unified teamwork during meetings and presentations. The D6520 has a 4K display that gives you all the space you need to share ideas. The multi-touch screen uses InGlass™, Optical bonding technology that allows you to precisely annotate documents and get your ideas across with clarity.

Collaboration Board for medium space and regular meetings

- 4K interactive screen
- Landscape usage
- Plug and share your laptop
- Motion detection
- Compatible with any video conference camera
- Enhanced features with Windows controller



Landscape orientation

Available Colours

4K
FULLHD

PRODUCT HIGHLIGHTS

MEDIUM LARGE
MEETING ROOM

FLOOR STAND
VESA MOUNT

VIDEO
CONFERENCE
READY
AND REALTIME
CONTENT
SHARING

MOTION
DETECTION

SMART
DEVICE
CONNECTIVITY

INTERACTIVE
SOFTWARE &
APPLICATIONS

Some features are supported by Ricoh Standard controllers only

Board Sheet

Category	Item	D6520	
Display Panel	Panel Size	65 inch	
	Aspect Ratio	16:9	
	Back Light	DLED	
	Max Resolution [dot]	3,840 x 2,160 dot (4K)	
	Max Display Color	1.07 Billion colors	
	Pixel Pitch [mm]	0.372(H) x 0.372(W)	
	Brightness [cd/m ²] (typ.)	440	
	Contrast Ratio (typ.)	5000:1	
	Angle of View [deg] (typ.)	left-right:178 upper-lower:178	
	Active Screen Size [mm]	1,428.48(H) x 803.52(V)	
	Response Speed [ms]	8(Typ)	
	Color	White	
	Display Orientation	Landscape	
	Touch Sensor	Technology	InGlass™, Optical bonding
Touch Point		Pen&Finger: 4 points (φ 2 - 8mm) Finger&Small Eraser: 20 points (φ8- 50mm) Larger Eraser: 2 points (φ50mm -) Total (Max): 20 points	
Resolution		Time Resolution: 150pt/sec Reported Resolution: 19353x10886 (landscape)	
Accuracy		Center area: 1mm (Typ) Edge area: 1.2mm (Typ)	
Touch Pen Request		2.0mm	
OS		Multi Touch	Windows 8 / 8.1 Windows 8 / 8.1 Pro Windows 8 / 8.1 Enterprise Windows Embedded Standard 7 P Windows Embedded Standard 8 Windows 10 Home Windows 10 Pro Windows 10 Enterprise Windows 10 IoT
		Single Touch	Windows 8 / 8.1 Windows 8 / 8.1 Pro Windows 8 / 8.1 Enterprise Windows Embedded Standard 7 P Windows Embedded Standard 8 Windows 10 Home Windows 10 Pro Windows 10 Enterprise Windows 10 IoT
			Mac OS X 10.8 -Mac OS X 10.15
		Touch Output	USB 3.0 (Type B)*
Cover Glass		Thickness [mm]	2mm
	Coating	Pre-treated AG (Anti-Glare) AF (Anti-Fingerprint)	
	Hardness [H]	7	

Motion Detection Sensor		Yes	
Remote Control Sensor		Yes	
Dust Resistant Function		IP5X equivalent	
Power Supply	Power Supply	100-240V, 50-60Hz	
	Power Consumption [W]	In Operation	Less than 300W (without OPS) Less than 380W (Fully configured)
		Standby	Less than 0.3W (without OPS)
Sound	amp [W]	12+12	
	Internal Speaker	Stereo (12+12)	
	Input	L/R, RCA	No
		Line3.5mm	1
	Output	L/R, RCA	No
Speaker-out		1□Headphone-Out	
Video	Input	VGA (Mini D-SUB 15pin)	1
		HDMI	1
		DVI-D	No
		DisplayPort	1
		Composite	No
	Output	Component	No
		S-Video	No
		VGA	No
		DVI	No
		DisplayPort	1
USB Hub(1)	I/F	USB3.0	
	Port	USB3.0: 2port(1.5A/port) TypeA	
	Power Supply	Self Powered	
USB Hub(2)	I/F	USB3.0	
	Port	USB3.0: 4port(1.5A/port) TypeA	
	Power Supply	Self Powered	
Control	Input	RS-232C	1
	Output	RS-232C	1
	RJ45 (Wired LAN)		No
	USB3.0 (Type B) *for Touch Sensor		USB3.0 (Type B) x 1
OPS Slot		1	
Operation Key		Tact switch x 7	
Product Size (W x D x H) [mm]		1,508 (W) x 83 (D) x 920 (H) (Landscape)	
Product Weight [kg] [Max]		45 47	
Installation		VESA 400(W) x 400(H)mm M8 x 16mm (depth)	
Environmental Condition	Operating Temperature Limits [°C]	0 - 32°C	
	Operating Humidity Limits [%]	10 - 80%RH	
	Storage Temperature Limits [°C]	-10 - 50°C	
	Storage Humidity Limits [%]	15 - 80%RH	
	Noise (dB)	Less than 35	

Ricoh D6520

Controllers

Category	Item	Specification		
Main Spec (OPS)	Development Name	STANDARD CONTROLLER	SMART CONTROLLER OP5	SMART CONTROLLER OP10
	Product Name	RICOH Collaboration Board Controller Type 3	RICOH Interactive Whiteboard Controller OP-10	RICOH Interactive Whiteboard Controller OP-5
	CPU	Intel Core i5-6500TE	Intel Core i7-6700TE	Intel Core i5-6500TE
	System OS	Windows 10 IoT Enterprise LTSC 2019 64-bit	Windows 10 Professional 64-bit	Windows 10 Professional 64-bit
	SSD	128 GB	512 GB	128 GB
	RAM Memory	8 GB	16 GB	8 GB
	Chipset	H110	Q170	H110
	LAN Interface (Wired)	10BASE-T/ 100BASE-TX/ 1000BASE-T	10BASE-T/ 100BASE-TX/ 1000BASE-T	10BASE-T/ 100BASE-TX/ 1000BASE-T
	LAN Interface (Wireless)	802.11 ac/a/b/g/n	802.11 ac/a/b/g/n	802.11 ac/a/b/g/n
	Interface (Output)	HDMI x 1	HDMI	HDMI
	Interface (Input)	VGA x 1 DisplayPort x 1 HDMI x 1	VGA x 1 DisplayPort x 1 HDMI x 1	VGA x 1 DisplayPort x 1 HDMI x 1
	Interface (Others)	USB 3.0 Type A x 3, 3.5 mm microphone jack, 3.5 mm headphone jack	USB 3.0 Type A x 3, 3.5 mm microphone jack, 3.5 mm headphone jack	USB 3.0 Type A x 3, 3.5 mm microphone jack, 3.5 mm headphone jack
	Bluetooth	Embedded	Embedded	Embedded
	Recovery Time from Standby Mode	About 65 seconds	About 6 seconds	About 6 seconds
Power Source	DC +12 to 19V	DC +12 to 19V	DC +12 to 19V	
Capture Box		Included (4K)	Not included	Not included
Installation		Insert into OPS slot	Insert into OPS slot	Insert into OPS slot
Product Size (W x D x H) [mm]		200 x 119 x 30 (OPS itself)	200 x 119 x 30	200 x 119 x 30
Product Weight [kg]		1.0kg (OPS), 0.3kg (Capture Box)	1.0kg (OPS)	1.0kg (OPS)
Environmental Condition	Operating Temperature Limits	0 - 32	0 - 32	0 - 32
	Operating Humidity Limits	10 - 80%	10 - 80%	10 - 80%
	Storage Temperature Limits	-10 - 50	-10 - 50	-10 - 50
	Storage Humidity Limits	15 - 80%	15 - 80%	15 - 80%

Capture Box Capture Box Specification

Item	4K Capture Box
Interface (Input)	HDMI 1.4b / DP 1.1 / VGA
Resolution (Output)/fps	30fps @ 4K/2K
Resolution (Input)/fps	30fps @ 4K / 60fps @ 2K
Audio Sampling Rate	48kHz @ 16/24bit □Hardware: 44.1kHz, 32kHz□
Non-HDCP Contents Display via Mac PC	HDMI/DP
Color Image	YUV422@2K / YUV420@4K
Time to Display via Capture Box	VGA/HDMI: 5sec DP: 7sec
Delay to Display	100msec
Dimension (W x D x H) [mm]	165 x 115 x 30 (Capture Box itself)
Input Detection via Converter	Automatic

Ricoh D6520

Options

Controllers

RICOH Collaboration Board Controller Type 3

RICOH Smart Controller OP5

RICOH Smart Controller OP10

Floor Stand

RICOH Collaboration Board Stand Type 7

Writing Tools

RICOH Collaboration Board Touch Pen Type 3

RICOH Interactive Whiteboard Eraser Type 1

RICOH Interactive Whiteboard Remote License Type 1

Software

RICOH IWB PLUGIN FOR O365 (Controller Type3 required)

RICOH COLLABORATION SOFTWARE RICC (Controller OP5/10 required)

Compliance

Supported Standards

SAFETY STANDARDS

UL62368-1; CAN/CSA-C22.2

EN62368-1; (CE marking)

EN60950-1 / EN62368-1 (TUV)

IEC60950-1 / IEC62368-1 (CB attestation)

CNS14336 (RPC)

KC Mark

GB4943 (CCC)

CU-TR

EMC

FCC Part15 SubpartB

IC ES-003

EN55024 (CE marking),EN55032 (CE marking)

EN55024,EN55035,EN55032,EN61000-3-2,EN61000-3-3

AS/NZS CISPR32 (C-Tick)

GB9254, GB17625.1 (CCC)

CNS13438 (RPC)

CU-TR (EMC)

EMF

EN62311 (CE marking)

Accessories

Remote Controller

Power Cord (longer than 2.5m)

VGA Cable (3.0m)

USB Cable 3.0 (1.8m)

HDMI Cable 2.0 (4.6m)

Ricoh D6520

Ricoh D6520

Dimensional
Drawing

